

2 poli

3000 rpm

Putere		Model		Turatie	Curent Nominal	Curent Pornire	Cuplu Nominal	Cuplu Pornire	Cuplu Maxim	Moment Inertie	Greutate
kW	CP			rpm	In (A) 400V 50Hz	Ip/In	Mn	Mp/Mn	Mmax/Mn	J (Kgm ²)	m (Kg)
0.09	0.12		56A2	2670	0.35	6	0.32	2.2	2.4	0.0001	2.8
0.12	0.16		56B2	2730	0.4	6	0.42	2.2	2.4	0.0001	3.2
0.18	0.25		56B2	2750	0.56	6	0.63	2.2	2.4	0.0001	3.5
0.18	0.25		63A-2	2710	0.55	6	0.63	2.2	2.4	0.0001	4
0.25	0.34		63B-2	2710	0.71	6	0.88	2.2	2.4	0.0002	4.4
0.37	0.5		63B-2	2710	1.05	6	1.3	2.2	2.4	0.0002	4.9
0.37	0.5		71A-2	2730	0.97	6	1.3	2.2	2.4	0.0003	5.6
0.55	0.75		71B-2	2760	1.42	6	1.9	2.2	2.4	0.0004	6.1
0.75	1		71B-2	2730	1.83	6	2.63	2.2	2.4	0.0005	7
0.75	1		80A-2	2770	1.77	6	2.59	2.2	2.4	0.0008	9.1
1.1	2		80B-2	2770	2.51	6	3.79	2.2	2.4	0.0010	10.2
1.5	2		80B-2	2800	3.32	6	5.12	2.2	2.4	0.0013	11.7
1.5	2		90S-2	2840	3.28	6	5.05	2.2	2.4	0.0014	12
2.2	3		90L-2	2840	4.61	6	7.4	2.2	2.4	0.0017	15
3	4		90L-2	2840	6.1	6	10.09	2.2	2.4	0.0021	18.5
3	4		100L-2	2840	6.03	7	10.09	2.2	2.3	0.0036	22.3
4	5.5		100L-2	2850	7.88	7.5	13.41	2.2	2.3	0.0044	25.2
4	5.5		112M-2	2880	7.88	7.5	13.27	2.2	2.3	0.0054	26.7
5.5	7.5		112M-2	2880	10.53	7.5	18.25	2.2	2.3	0.0068	30.2
5.5	7.5		132SA-2	2900	10.53	7.5	18.12	2	2.2	0.0119	38.5
7.5	10		132SB-2	2920	14.14	7.5	24.54	2	2.2	0.0133	42.2

9.2	12.5		132M-2	2930	17.25	7.5	30	2	2.2	0.0157	51.4
11	15		132M-2	2930	19.96	7.5	35.87	2	2.2	0.0176	60.4
11	15		160MA-2	2930	20.1	6.7	35.8	2.6	2.9	0.0380	101
15	20		160MB-2	2930	27.2	6.7	48.8	2.6	2.9	0.0450	111
18.5	25		160L-2	2930	32.9	6.8	60.4	2.5	2.8	0.0550	126
22	30		160L-2	2930	38	6.8	71.4	2.5	2.8	0.0700	158
22	30		180M-2	2940	38.9	6.6	71.4	2.6	2.8	0.0760	176
30	40		180 M-2	2950	52.8	6.6	96.9	2.6	2.8	0.0760	190