

DATE TEHNICE

8 poli

750 rpm

Putere		Model	Turatie	Curent Nominal	Curent Pornire	Cuplu Nominal	Cuplu Pornire	Cuplu Maxim	Moment Inertie	Greutate
kW	CP		rpm	In (A) 400V 50Hz	Ip/In	Mn	Mp/Mn	Mmax/Mn	J (Kgm ²)	m (Kg)
0.09	0.12	71A-8	680	0.48	3	1.26	1.5	1.7	0.0008	6
0.12	0.16	71B-8	690	0.58	2.7	1.66	1.6	1.7	0.0010	6.8
0.18	0.25	80A-8	680	0.84	2.8	2.53	1.5	1.7	0.0021	9.9
0.25	0.34	80B-8	680	1.06	2.7	3.51	1.6	2	0.0025	10.9
0.37	0.5	90S-8	680	1.35	2.8	5.2	1.6	1.8	0.0038	14.8
0.55	0.75	90L-8	680	1.85	3	7.73	1.6	1.8	0.0047	17.2
0.75	1	100LA-8	710	2.45	3.5	10.09	1.7	2.1	0.0061	17.5
1.1	1.5	100LB-8	710	3.2	3.5	14.8	1.7	2.1	0.0075	19.7
1.5	2	112M-8	710	4.3	4.2	20.19	1.8	2.1	0.0129	25.6
2.2	3	132S-8	720	5.96	5.5	29.2	2	2	0.0298	35.5
3	4	132M-8	720	7.7	5.5	39.81	2	2	0.0387	45
4	5.5	160MA-8	720	9.7	4.4	53.1	2.2	2.5	0.0750	90
5.5	7.5	160MB-8	720	12.9	5	73	2.2	2.4	0.0930	102
7.5	10	160L-8	720	16.8	5.7	99.5	2.1	2.3	0.1260	122
11	15	180L-8	720	24.1	5.6	144	2.3	2.5	0.2030	150
15	20	200L-8	730	32.3	5.5	196.3	2.1	2.4	0.3390	212